

Irrigators accessories at page 20



MODEL	PIPE DIAMETER mm	PIPE LENGTH mt
<b>B200 ECO</b>	75	340
	75	400
	82	320
	82	360
	82	400
	90	260
	90	300
	90	350
	90	370
	100	210
	100	250
	100	270
	100	300
110	200	

MODEL	PIPE DIAMETER mm	PIPE LENGTH mt
<b>B200 EVO</b>	75	340
	75	400
	82	320
	82	360
	82	400
	90	260
	90	300
	90	350
	90	370
	100	210
	100	250
	100	270
	100	300
110	200	

**MAIN FEATURES**



Efficient turbine drive mounted in monobloc with the gearbox; 4 speed gearbox equipped with automatic drive disengagement and assistance quick hose rewinding; Safety devices for PTO and rewinding out of the drum; Moving transmission to the reel through toothed crown of large diameter; Lead screw hose layering device; Automatic and manual by-pass; Speed control; Pressure gauge and hours meters; Large diameter 360° slewing ring; Rotation device directly setting by hydraulic trolley lift; Hydraulic trolley lift and stabilizers (mechanical on models B200ECO); Supplementary stabilizers on the drawbar; Hot galvanised lower and upper frame; Galvanised water-course and accessories; 3 wheel galvanised sprinkler-trolley with adjustable track (on request, with 2 wheels and backslide); Accident protections; Sprinkler with set of nozzles; High resistant "Medium density" PE-hose with differentiated thickness from Ø 90mm; Instructions and maintenance handbook; Guarantee coupon.

**EQUIPMENT**

