



2 Poles compound IP23 KVA

| | | |
|-----------|-------|------|
| C.2.18.23 | IP 23 | 18,0 |
| C.2.30.23 | IP 23 | 30,0 |

2 Poles brushless AVR IP23 KVA

| | | |
|------------|-------|------|
| BA.2.30.23 | IP 23 | 30,0 |
| BA.2.40.23 | IP 23 | 40,0 |
| BA.2.50.23 | IP 23 | 50,0 |
| BA.2.60.23 | IP 23 | 60,0 |

4 Poles brushless AVR IP23 KVA

| | | |
|------------|-------|------|
| BA.4.30.23 | IP 23 | 30,0 |
| BA.4.40.23 | IP 23 | 40,0 |
| BA.4.50.23 | IP 23 | 50,0 |
| BA.4.60.23 | IP 23 | 60,0 |
| BA.4.90.23 | IP 23 | 90,0 |

2 Poles compound IP44 KVA

| | | |
|-----------|-------|------|
| C.2.18.44 | IP 44 | 18,0 |
| C.2.30.44 | IP 44 | 30,0 |

4 Poles brushless AVR IP44 KVA

| | | |
|------------|-------|------|
| BA.4.30.44 | IP 44 | 30,0 |
| BA.4.45.44 | IP 44 | 45,0 |
| BA.4.55.44 | IP 44 | 55,0 |
| BA.4.65.44 | IP 44 | 65,0 |
| BA.4.80.44 | IP 44 | 80,0 |

FEATURES

The quality of POWERTRAC series pto-driven generating sets is the result of the integral Nettuno design, of the best selection of components, precise assembly and computer controlled load and factory tests for each genset. This will guarantee the maximum reliability, quality and performance.

STANDARD EQUIPMENT

BASE FRAME: steel construction, hot painting, 3 points mounting for tractor. CONTROL PANEL: steel construction, instruments visibility from tractor. GEAR BOX: hardened and tempered steel construction, permanent oil lubrication, cooling wings.



EQUIPMENT

